

























**POROSITËSI**



B.O.E. "TAULANT" sh.p.k. & "HMK-Consulting" sh.p.k.

**GRAFIK PUNIMESH**  
**FAZA PROJEKT ZBATIM**

**EMERTIMI I PROJEKTIT: RIGJENERIMI URBAN I BULEVARDIT TË PALMAVE DHE AGRUMEVE , PËRGJATË " SHKOLLËS HALIM XHELO " , NË DREJTIM TË " BULEVARDIT , " ISMAIL QEMALI " , VLORË**

Nr.	Analize	Pershkrimi i Punimeve	Muaji 1	Muaji 2	Muaji 3	Muaji 4	Muaji 5	Muaji 6	Muaji 7	Muaji 8	Muaji 9	Muaji 10	Muaji 11	Muaji 12	
	Analize	F.V Kamera IP autodome e jashteme, PTZ, Resolution: 1920x1080, Scan: Progressive, Color representation: complies with ITU-R BT.709, Aspect ratio: 16:9, Frame rate: 25 and 30 frames/s, Lens 30x zoom 4.5 mm - 135 mm (F1.6 - F4.4), Optical Zoom Field of View (FOV) 2.4° - 60.9°, Focus Automatic with manual override, Iris Automatic with manual override, Digital Zoom 16x, Color 0.05 lx, Mono 0.01 lx, With IR 0 lx, Day/Night Mechanical switchable IR filter (Auto/On/off) Monochrome, Number of LEDs 4 Wavelength 850 nm Distance 180 m (590 ft) (Detection) Beam angle Wide beam: 36° Narrow beam: 6.3°, Video compression H.265 H.264 M-JPEG, Frame rate 60fps at all resolutions, Resolution 1080p.													
	Analize	F. Shtyllë 12 mt alumini e paisur me automat per mbrojtjen e ndricuesit , e certifikuar per instalim ne ambjent me perqendrim te larte te kriqerave													
	Analize	F.Rack 12HU, per instalime te jashteme, prej celiku te pandryshkshem ( INOX), I montuar mbi strukture betoni.													
	Analize	F. Blloku elektrik 1HU me 6 shuko individuale dhe nderperes qarku													
	Analize	F. 1HU Switch 24 Porta me 2 Ethernet/SFP Uplink ports, portat SFP te perfshira, perfshi aksesoret e montimit													
	Analize	F. Artopallant (Music Horn Loudspeaker) per montim te jashtem, I perbere me material Glass Reinforced Polyester (GRP) IP 67 housing per mbrojtje nga uji, pluhurat, kripes dhe klorit, 22,5W, Power tapping 15 / 7.5 / 3.75 / 1.87 W, Sound pressure levelat rated power / 1 W (1 kHz, 1 m) 120 / 108 dB (SPL), Effective frequency range(- 10 dB) 300 Hz to 9 kHz, Rated input voltage 70 / 100 V, Dimensions (L x D max) 302 x 212 mm(11.89 x 8.35 in), i kompletuar me aksesore per													
	Analize	F.Riprodhues muzike I amplifikuar (CD,RADIO,USB) perfshire aksesoret e montimit dhe thirrjen audio te Evakuimit I kompletuar gati per pune,													
	Analize	F. Mixer per evakuimin 3 zona me amplifikator te integruar, perfshire aksesoret e montimit ne rack I kompletuar gati per pune,													
	Analize	F. Mikrofon me kontroll per 6 zona per njoftime manuale I kompletuar gati per pune,													
	Analize	F. Shtyllë 12 mt alumini e paisur me automat per mbrojtjen e ndricuesit , e certifikuar per instalim ne ambjent me perqendrim te larte te kriqerave													
		<b>Shuma Pajisjet</b>													
		<b>Totali</b>													

**Projektues:**

B.O.E."TAULANT" sh.p.k. & "HMK-Consulting" sh.p.k.

**Përfaqësues me prokurë:**

Inxh. Ditika QATIPI