



REPUBLIKA E SHQIPERISE
BASHKIA TIRANE

Specifikime Teknike per Sistemin e Kamerave

“ Rikonceptim i Kopshtit Zoologjik, Ndertesat ,,

Specifikime teknike SW 24 porta Ethernet dhe 4 porta SFP

Product Features

- Non-blocking Layer 2 switching capacity
- 16K host table
- IEEE 802.1Q VLAN
- Supports up to 4K simultaneous VLANs
- Port isolation
- Port security
- Broadcast storm control
- Port mirroring of ingress/egress traffic
- STP / RSTP / MSTP
- Access Control List
- MikroTik neighbor discovery
- SNMP
- 10218-byte jumbo frames support
- IGMP snooping
- IEEE 802.3ad and static link aggregation

Product Specifications

- CPU: Dual-Core ARM v7 800 MHz:
- RAM: 512 MB
- Storage type: Flash
- Storage size: 16 MB
- Switch chip model: 98DX3236A1
- 10/100/1000 Ethernet ports: 24
- SFP+ cages: 4
- Operating system: SwOS / RouterOS (Dual boot)
- Supported input voltage: 100 - 240 V
- Dimensions: 443 x 305 x 44 mm
- Operating temperature: -20°C .. +60°C tested
- Max power consumption: 44 W
- Serial port: RJ45
- License Level: 5

Quick Specifications

- 24 Gigabit Ethernet ports
- 4 SFP+ ports
- RJ45 serial console port
- Non-Blocking throughput: 64 Gbps
- Switching capacity: 128 Gbps
- Forwarding rate: 95.2 Mpps
- Maximum power consumption: 44 W (without PoE devices connected)
- Supports PoE+ IEEE 802.3at/af and 24 V Passive PoE)
- Temperature based fan control
- 1U rackmount