

24	3.332	Gabion me rrjete tel xingato (1.5x1x1) m	
25	3.333	Gabion me rrjete tel xingato (2x1x1) m	
26	3.338	Gabion me rrjete tel xingato (2x1x0.5) m	
27	3.352	Mbushje me gure kave per prizem	
28	3.643	Mbjellje skarpate me bar	
II Punime per shkarkuesin katastrofik te diges Bejn 2			
1	3.59/a	Germim me eksk. shkemb i bute per kanal	
2	3.183/a	Shtrese zhavorri ne beton t = 10 cm	
3	3.243	Beton C 16/20 per lug b/a	
4	3.287	F V hekur betoni i zakonshem Ø 6 ~ 10mm	
5	3.288	F V hekur betoni i zakonshem Ø > 12mm	
6	3.An/fh	F V waterstop tip RT 2000 10*20 & h/izolues tip rapid cement ne bashkimin e kampatave b/a.	
7	3.47/1c	Mbushje, rafshim,ngjeshje me tokmak elektrik, cdo 30 cm, toke te forte	
8	3.243	Beton C 16/20 per uren	
9	3.288	F V hekur betoni i zakonshem Ø > 12mm per uren	
III Punime per ujeleshuesin			
1	2.426/5	Prishje mure betoni	
2	An. 4	Kontroll me sonde skanuese lazer i tubit te ujeleshuesitt	
3	3.59/a	Germim me eksk. shkemb i bute per puseten	
4	3.183/a	Shtrese zhavorri t = 10 cm	
5	3.243	Beton C16/20 per bazamentin	
6	3.243	Beton C16/20 per mure	
7	3.396/1	Mbushje me zhavorr pas mureve	
8	1.100/p	Zgare metalike	
9	4.6	F.V.tub çeliku Ø 350/8 mm	
10	3.624	H / Izolim me emulsion, 2 duar bitum i tubit	
11	An.8	F.V. saracineske PN 16 DN 350	
12	2.491/l	FV Tuba e rakorderi ujesjellesi PE d=250mm, t = 18.4 mm, Pn 10	
IV Punime per rrugen e aksesit ne objekt L-400 ml			
1	3.101/b	Germim eksk.0.5 m ³ me shkarkim ne toke per rrugen	
2	3.119/b	Germim eksk.0.5 m ³ shkemb i coptuar per rrugen	
3	3.211	Shtrese çakelli mbeturine kave t=20cm, perhapur e ngjeshur me makineri	
4	3.212/b	Shtrese stabilizant t=10cm	
5	3.25/a	Germim toke e forte me krah ne kanal anesor.	
	3.164/1t	F V tuba te brinjezuar HDPE SN8 d=315 mm	
	3.243	Struktura monolite betoni C 16/20	

"TRIANGLE" sh.p.k
 Drejtues Teknik & Ligjor
 Ing. Zenulla MEHMETI
 PROJEKTIM-MBAIKQYRJE - KOLAUDIM
TRIANGLE SH.P.K
 NIF T: M17305701T